

KÄRCHER

makes a difference



CLEANING TECHNOLOGY FOR INDOORS.

Quiet, indoor cleaning for commercial applications.

HDS CABINET



Cleaning technology for indoors.

This Kärcher all-electric hot water pressure washer introduces hot-water tank technology to deliver hot water on demand ideal for indoor cleaning. Water is heated by flowing through a coil inside an 80-gallon water tank. Heating elements generate 138,000 BTU to produce hot water of up to 180°F. Both models are ETL and CSA certified.



1 Powerful and durable

- Industrial-grade, tri-plunger, oil-bath, belt-drive, Kärcher pump with 7-year warranty and cast iron pulley system that features cool operating V-belts and an easy-to-adjust TrueTrak belt tension device.
- Heavy-duty, steel cabinets are protected by an epoxy powder-coat finish; upper cabinet ventilated for cool operation.
- Thermal pump saver valve prevents damage by venting recirculated water.
- Nine heating elements (40.5 KW) are protected by an Incoloy alloy sheath so they do not come in contact with the pressurized water, which can cause scale build up.
- Industrial-duty magnetic motor starter for reliable operation.
- 50 ft. of 1wire, non-marking hose rated for up to 4500 PSI; hose guard provides burst protection.
- Low-water flow switch prevents damage to heating elements due to lack of water.

2 Smart features

- Industrial-duty electric motor with thermal overload protection.
- Three quick-coupler nozzles are made of hardened stainless steel and mounted for easy operator access.
- Easy-to-attach detergent Injector for ease in introducing soap into the spray while cleaning.
- 7-day timer automatically turns off heating elements to conserve energy.
- EASY!Force trigger gun with cruise control like technology uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.
- ETL certified to the rigorous UL-1776 safety standards.
- Hour meter for easily monitoring hours of use and better scheduled maintenance.

Technical data and equipment.

TECHNICAL DATA

| Model | Part No. | GPM | PSI | Drive | HP | Electrical | Amps | Pump | Ship Weight (lbs) | Ship Dimensions (L x W x H) Inches |
|-----------------|-------------|-----|------|-------|-----|------------|------|------------|-------------------|------------------------------------|
| HDS 4.0/20 E Ec | 1.109-075.0 | 4.2 | 2000 | Belt | 6.2 | 460V / 3ph | 55 | Kärcher KM | 640 | 32 x 24 x 52 |
| HDS 4.0/30 E Ec | 1.109-076.0 | 3.5 | 3000 | Belt | 7.5 | 460V / 3ph | 59 | Kärcher KM | 640 | 32 x 24 x 52 |
| HDS 4.0/20 E Ef | 1.109-956.0 | 3.5 | 2000 | Belt | 5 | 575V / 3ph | 46 | Kärcher KM | 620 | 34 x 25 x 52 |
| HDS 4.0/30 E Ef | 1.109-957.0 | 3.5 | 3000 | Belt | 7.5 | 575V / 3ph | 49 | Kärcher KM | 640 | 34 x 25 x 52 |

ACCESSORIES

| Order No. | Description |
|---|---|
| <input checked="" type="checkbox"/> 8.756-481.0 <input checked="" type="checkbox"/> | EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose. |

OPTIONS (FACTORY INSTALLED)

| Order No. | Description |
|--|--|
| <input type="checkbox"/> 8.925-520.0 | Time delay shutdown (replaces auto start-stop) (only for 460V units) |
| <input type="checkbox"/> 9.801-002.0 | Pressure washer stainless steel cabinet (only for 460V units) |
| <input checked="" type="checkbox"/> Included <input type="checkbox"/> Optional <input checked="" type="checkbox"/> Not compatible with EASY!Lock | |

Please contact us for more information:

Kärcher U.S.A.

6398 N. Kärcher Way
Aurora, CO 80019
U.S.A.

Phone 888-805-9852

Fax 800-248-8409

www.karcher.com/us

Kärcher Canada

275 Pendant Drive
Mississauga, ON L5T 2W9
Canada

Phone 888-705-9444

Fax 905-672-3155

www.karcher.ca